Architect A Blue Reader

Architect Range

Product Image	
Part number	7257713 – Architect A Blue - RFID & Bluetooth Standard Reader
Dimensions	W 80 x H 107 x D 26mm
RFid Frequency	High Frequency (13.56 MHz: ISO14443A types A & B, ISO18092) Bluetooth / NFC
PAC ID Devices	PAC Ops™ Lite, PAC Ops™
Programmable Output Formats	PAC, PAC64
Maximum Read Range	80mm for PAC HF ID Devices 20m for Mobile IDs (configurable)
Vandal Resistance	IK10 certification
Environment	IP65 – Indoor/Outdoor weather resistant
Power	7 – 28V DC, 150mAmp @ 12V DC
Operating Temperature	-30 to 70 °C
Operating Humidity	0-95% Relative humidity
Audio/Visual Indicators	Audible Sounder and 2 x RGB LEDs (360 configurable colours)
Tamper Output	Accelerometer-based tamper detection system with key deletion option (patented solution)
Recommended Cabling	PAC output - 6 core 24 AWG alarm cable (unscreened)
Material	UL Rated ABS Plastic
Certification	CE / FCC/ UL compliant
Warranty	Lifetime against electronic failure

Date of print/release: (July 2020)
This document is provided by STANLEY Security or its affiliates ("STANLEY") for general information purposes only. STANLEY warrant the accuracy of the data as at the date of print/release, but it may be subject to change after such date. STANLEY will not be responsible for any loss or damage that may arise from reliance thereof. Copyright © STANLEY Security 2020. PAC, GDX and 3xLOGIC are the trade marks of STANLEY Security, Stanley Black & Decker, Inc., or their affiliates.

Ordering Information:
PAC Access Control, 1 Park Gate Close,
Bredbury, Stockport, Cheshire, SK6 2SZ
customerservices@pacgdx.com | +44 (0) 161 406 3400
www.pacgdx.com